

DEPARTMENT OF THE ARMY
Omaha District, Corps of Engineers
106 South 15th Street
Omaha, Nebraska 68102-1618

:NOTICE: Failure to acknowledge : Solicitation No. DACW45 03 B 0002
:all amendments may cause rejec- :
:tion of the bid. See FAR : Date of Issue: 13 Nov 2002
:52.214-3 of Section 00100 : New Date of Opening: 31 Jan 2003

Amendment No. 0004
23 January 2003

SUBJECT: Amendment No. 0004 to Specifications and Drawings for Construction of
RIVER CONTROL STRUCTURE MODIFICATIONS, MISSOURI RIVER, NEBRASKA CITY
TO PERU, NE.

Solicitation No. DACW45 03 B 0002.

TO: Prospective Bidders and Others Concerned

1. The specifications and drawings for subject project are hereby modified as follows (revise all specification indices, attachment lists, and drawing indices accordingly).

a. Specifications. (Descriptive Changes.)

(1) Page 00010-1, delete date and time of bid opening shown and substitute "31 Jan 2003" at "2:00".

(2) Section 02340 page 2, add the following new paragraph:

"3.4 PLACEMENT

3.4.1 Riprap

Riprap shall be placed on the bedding material within the limits shown on the drawings or as directed by the Contracting Officer's Representative. Riprap stone shall be placed in such manner as to produce a reasonably well-graded mass of rock with the minimum practicable percentage of voids. Riprap shall be placed to its full course thickness in one operation and in such manner as to avoid damage to the bedding material and to minimize segregation of the riprap. The larger stones shall be well distributed and the entire mass of stones in their final position shall be roughly graded to conform to the gradation specified. The finished riprap shall be free from objectionable pockets of small stones and clusters of larger stones. Placing riprap in layers will not be permitted. The desired distribution of the various sizes of stones throughout the mass shall be obtained by selective loading of the material at the quarry or other source ; by controlled dumping of successive loads during final placing and placement. All stone shall be placed by means of clam, orange peel, or skip box. However, zero drop height placement procedures are to be utilized for riprap stone to avoid displacing or damaging the underlying bedding. Dumping of stone at the top of slopes and rolling or pushing into place will not be permitted. Manipulating or moving stone at any time prior to placement by means of dozers or other blade equipment will not be permitted. Rearranging of individual stones by mechanical equipment or by hand will be required to the extent necessary to obtain a reasonably well graded distribution of stone sizes as specified

above.

3.5 PROTECTION

The Contractor shall maintain the riprap stone until accepted and any material displaced by any cause shall be replaced at his expense to the lines and grades shown on the drawings."

2. This amendment is a part of the bidding papers and its receipt shall be acknowledged on the Standard Form 1442. All other conditions and requirements of the specifications remain unchanged. If the bids have been mailed prior to receiving this amendment, you will notify the office where bids are opened, in the specified manner, immediately of its receipt and of any changes in your bid occasioned thereby.

a. Hand-Carried Bids shall be delivered to the U.S. Army Corps of Engineers, Omaha District, Contracting Division (Room 301), 106 South 15th Street, Omaha, Nebraska 68102-1618.

b. Mailed Bids shall be addressed as noted in Item 8 on Page 00010-1 of Standard Form 1442.

3. Bids will be received until 2:00 p.m., local time at place of bid opening, 31 Jan 2003.

U.S. Army Engineer District, Omaha
Corps of Engineers
106 South 15th Street
Omaha, Nebraska 68102-1618

23 Jan 2003
MFS/4411